



Transforming Presentation Environments



ACCESSIBLE CONNECTIVITY

Our technology is built with usability in mind. All G-Touch models come with an easily accessible front-facing connection panel, allowing simple plug & play connectivity with external devices. With the optional add-on of MirrorOps you can mirror devices wirelessly via WI-FI.

FRONT FACING SPEAKERS

The G-Touch range is designed to provide the ultimate presentation experience. Built-in, front-facing speakers provide crisp sound and negate the need for additional speakers or sound bars.

UPGRADEABLE BUILT-IN PC

Flexibility is key for evolving technology, and all G-Touch models have the option to add a built-in PC. Our simple 'slide and secure' fitting option allows for simple upgrades and is easily accessible.


SINGLE POWER CONTROL

No more fiddling around the side and back of the screen to find various ON/OFF buttons. All G-Touch models come with a single, front facing power button which powers the Screen.



Collaboration Innovation

www.geneeworld.com



Genee World


Product Specification

Description	55" Classic	65" Classic	70" Classic
Backlight	LED		
Display Area	1209.6 x 680.4mm	1428.5 x 803.5mm	1538.88 x 865.12mm
Display Ratio	16:9		
Resolution	1920 x 1080 Pixel		
Display Colours	8bit		
Viewing Angles	178°		
Brightness	370cd/m2	370cd/m2	380cd/m2
Touchscreen Glass	Physical steel mohs with class 7, toughened glass. 4mm; transmittance :>95%		
Speaker Output Power	15W x 2		
Power Consumption	Maximum <240W / Eco mode ≤120W / Standby mode ≤0.5W		
Touch Surface	Anti-glare (optional)		
Touch Sensor	Infrared		
HID Support	HID		
Touch Points	10 point touch		
Writing Tools	Pen or finger		
AV Inputs/Outputs	FRONT: HDMI in *1, USB for touch *1, USB for media player *1, USB for PC*2 (2.0*1; 3.0*1), MIC*1 REAR: USB for media player*1, USB for touch*1, HDMI in *2, VGA in *1, Audio in *1, AV in *1, YPBPR/YCBCr/audio IN*1, AV out*1, Audio out*1, RS232*1		
Touch Resolutions	32767*32767		
Scan Speed	8ms		
Cursor Speed	125 points		
Positioning Accuracy	1mm		
Communication Interface	USB		
Transmission Range	5m		
Front/side I/O port	Yes		
Hot Key Define	Manual, Source, Eco mode, VGA, HDMI, Volume + , Volume - , OPS power		
Android System	No		
Intellegent Light Detector	Yes		
Speaker Position	Front-facing		
OPS Slot	Yes		
Project Flow	Yes (Opt-Out available)		
Detachable IR Frame	Yes		

 ON-SITE REPAIR	 TILTABLE BRACKETS	 BUILT-IN WI-FI	 LIGHTWEIGHT DESIGN	 UPGRADEABLE FIRMWARE
---	--	---	---	---

Collaboration Innovation

Libra House, Upper Zoar Street, Wolverhampton, West Midlands WV3 0LA
 Telephone: +44 (0) 1902 390878 Email: sales@geneeworld.com



Genee World